

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 August 2005 (25.08.2005)

PCT

(10) International Publication Number
WO 2005/077604 A1

(51) International Patent Classification⁷: **B25B 27/06**

(21) International Application Number:
PCT/GB2005/000466

(22) International Filing Date: 10 February 2005 (10.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0402990.6 11 February 2004 (11.02.2004) GB

(71) Applicant and

(72) Inventor: FENTON, Paul [GB/GB]; 66 Clent Avenue,
Maghull, Merseyside L31 0AZ (GB).

(74) Agents: LYONS, Andrew, John et al.; Marks & Clerk,
Tower Building, Water Street, Liverpool L3 1BA (GB).

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

Published:
— with international search report

[Continued on next page]

(54) Title: APPARATUS AND METHOD FOR REMOVING FITTINGS FROM PIPES



(57) Abstract: Apparatus (10) for removing a friction grip fitting (56) from a pipe (50) comprises a first engagement means (16, 18) for directly or indirectly engaging the friction grip fitting, a second engagement means (34) for engaging the end of the pipe at a position spaced apart from the friction grip fitting and means (24) for applying a force to move the first and second engagement means with respect to one another to slide the friction grip fitting with respect to the pipe.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.